



GEOFIX



GDL28X Digital Level

Features:

- * The operation is simple and easy to learn
- * Take measurement automatically, the digital level enables accurate measurement by any operator with no experience.
- * The model is compact in shape and easy to carry.



5m barcode staff

Product Specification

| | |
|------------------------------------------------|---------------------------------------|
| Model No | GDL28X |
| Standard deviation for 1km double-run Leveling | |
| Electronic reading | 1.5mm/0.7mm |
| Optic reading | 1.5mm |
| Electronic reading system | |
| Max.distance measuring | 100m |
| Min. distance measuring | 2m |
| Measuring time for one time | 3s |
| Display | |
| Min.display value of altitude | 0.1mm |
| Min. display value of distance | 0.01m |
| Telescope | |
| Magnification | 28X |
| Objective aperture | 40mm |
| Shortest sighting distance | 0.5m |
| Compensation | |
| Operation range | ±15' |
| Setting time | 2s |
| Angle value of circular bubble | 8'/2mm |
| Interface of data communication | RS-232C |
| Power | 6V chargeable battery or 4*AA battery |
| Continuous working time | 38 hours |
| Working temperature | -20°C~+50°C |
| Weight | 2.5kgs |
| Size | 244mm*188mm*190mm |

