



GEOFIX



## **GDL32X**

### **Digital Level**

Features:

The operation is simple and easy to learn

\* Take measurement automatically, the digital level enables accurate measurement by any operator with no experience.

\*The model is compact in shape and easy to carry.

5m barcode staff

# Product Specification

<b>Model No</b>	<b>GDL32X</b>
<b>Standard deviation for 1km double-run Leveling</b>	
Electronic reading	1mm
Optic reading	1mm
<b>Electronic reading system</b>	
Max. distance measuring	120m
Min. distance measuring	2.5m
Measuring time for one time	<3s
<b>Display</b>	
Min. display value of altitude	0.1mm
Min. display value of distance	0.01m
<b>Telescope</b>	
Magnification	32X
Objective aperture	36mm
Shortest sighting distance	0.5m
<b>Compensation</b>	
Operation range	±15'
Setting time	2s
Angle value of circular bubble	8'/2mm
Memory storage capacity	16*200 points
Power	4*AAA battery
Continuous working time	18 hours
Working temperature	-10°C~+50°C
Net Weight	1.7 kgs
IP grade	IP55



YIWU GEOFIX GNSS CO.,Ltd  
 Email: [info@geofix.top](mailto:info@geofix.top)  
 Web: [www.geofix.top](http://www.geofix.top)  
 Edition: 202210